

M3

FEATURES / BENEFITS



M3F24-1



M3F24-2



M3F47-2



M3F47-4

- DIGITAL TEMPERATURE CONTROL SYSTEM
- SELF-DIAGNOSTIC SYSTEM
- COMPREHENSIVE DIAGNOSTICS DEFROST SYSTEM
- OVERSIZED AND BALANCED REFRIGERATION SYSTEM (R404A), FACTORY SEALED AND PRE-LUBRICATED FOR LONG LIFE
- HOLDS -10°F ~ 5°F
- 400 SERIES STAINLESS STEEL FRONT AND SIDES
- INTERIOR NSF APPROVED COATED ALUMINUM AND 300 SERIES STAINLESS STEEL FLOOR AND CEILING
- FOAMED-IN-PLACE POLYURETHANE HIGH DENSITY CELL INSULATION (CFC FREE)
- MINIMUM WATTAGE HEATER IN CABINET FRAME AND DOOR
- ERGONOMICALLY DESIGNED RECESSED DOOR HANDLES STANDARD
- SELF-CONTAINED SYSTEM NO PLUMBING REQUIRED

- * A certificated member of NMSDC
- * CEC. California Energy Commission Certificated
- * MEA. City of New York Building Department Approved



Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H
M3F24-1	1	24	3	1/2	7.8	290	28.7 x 30.9 x 78.0
M3F24-2	2	24	3	1/2	7.8	290	28.7 x 30.9 x 78.0
M3F47-2	2	47	6	3/4	10.5	420	51.7 x 30.9 x 78.0
M3F47-4	4	47	6	3/4	10.5	420	51.7 x 30.9 x 78.0
M3F72-3	3	72	9	1-1/4	10.4	635	77.8 x 30.9 x 78.0
M3F72-6	6	72	9	1-1/4	10.4	635	77.8 x 30.9 x 78.0

- Depth does not include 1-3/8" for rear condensate enclosure.
 - Height does not include 4" caster height or 6" optional legs.
 - Requires 115/208-230/60Hz, single phase, 3 pole, 4 wire circuit (models M3F72-3 & M3F72-6 only).
- Design and specifications subject to change without prior notice.